

TL Tube GFT8



LM 79
LM 80

Typenummer	Vermogen	Lumen / watt	Lumen	Beam angle	Color (K)	Lens	LED	CRI	Powerfact.	Size	Voltage	Garantie	Tech. Levens.
GFT8 - 130 - 0600	10 watt	130±5	1.300	130°	3000—6000	Frosted	SMD2835	>RA80	≥0.9	Ø26x0600	VAC90-265	5 jaar	50.000u
GFT8 - 130 - 1200	20 watt	130±5	2.600	130°	3000—6000	Frosted	SMD2835	>RA80	≥0.9	Ø26x1200	VAC90-265	5 jaar	50.000u
GFT8 - 130 - 1500	25 watt	130±5	3.250	130°	3000—6000	Frosted	SMD2835	>RA80	≥0.9	Ø26x1500	VAC90-265	5 jaar	50.000u
GFT8 - 160 - 0600	09 watt	160±5	1.440	130°	3000—6000	Frosted	SMD2835	>RA80	≥0.9	Ø26x0600	VAC90-265	5 jaar	50.000u
GFT8- 160 - 1200	20 watt	160±5	3.200	130°	3000—6000	Frosted	SMD2835	>RA80	≥0.9	Ø26x1200	VAC90-265	5 jaar	50.000u
GFT8 - 160 -1500	25 watt	160±5	4.000	130°	3000—6000	Frosted	SMD2835	>RA80	≥0.9	Ø26x1500	VAC90-265	5 jaar	50.000u

Optional	Lens	Clear (beam angle 120°)
	Ballast Compatibel	See our series GFT8BC
	Micro (motion) sensor	See our series GFT8MS

U kunt ons bereiken via:

☎ 0229 571 526

✉ info@green-facility.nl

🌐 www.green-facility.nl